

PS535FC-Lite Marketing Specifications

A Fully Rugged GPS PDA

Physical Characteristics	Length: 5.68 in. (144.25 mm) Height: 1.15 in. (29.3 mm)	Width: 3.24 in. (82.25 mm) Weight: 10.58 ounce (300 grams)
Environmental	Operating temp: -4°F to 140°F (-20°C to 60°C) Relative humidity: 5% to 95% (non-condensing) Drop spec: 5 ft., (1.52 meter) MIL-STD 810F Tumble: 1,000 1.6 ft./0.5 m tumbles at room temperature (2,000 hits)	Storage temp: -22°F to 158°F (-30°C to 70°C) Rain and dust resistance: IP54 compliant
Power	Rechargeable 3.7 volt 2400 mAh Li Ion battery pack Up to 8 hr usage (typical; reduced in freezer applications)	
Operating System	Microsoft® Windows® Mobile 6.1	
Microprocessor	Samsung 2450 processor, 533 MHz	
Memory and Storage	On-board RAM: 128MB MDDR	On-board ROM: 2GB NAND FLASH
Internal Slots	(1) For SD, SD I/O (support 4bit SDIO) and compatible with MMC cards (with dummy insert) (2) Support Maxmum Memory Card Size : 8GB	
Display	Anti-glare 3.5" VGA resolution with high brightness, 65K colors and Touchscreen	
Standard Communications	USB Client (for sync and battery charge) Headphone Build in Mic	GPS MMCX Antenna Connector Speaker
Integrated Radio Options	802.11b/g(China version will be locked)	Bluetooth v2.0
GPS	SiRF StarIII chipset	
Button	4 Quick keys	1 five-way joystick
Warranty	3 Yeas on limited warranty, parts & labor	
Accessories	AC Adapter with US/EU/UK Plug Mini USB Cable Hand Strap Screen Protector	Microsoft GettingStartedDisc & Getac Manual Quick Start Guide Service Information and Warranty Card
Optional Accessories	Vehicle Charger Vehicle Mount - Cradle & Pedesta External GPS Antenna AC ADPT	STYLUS PEN HANDSTRAP PANEL PROTECT FILM Carry Bag
Suggested Accessories List	SocketMobile Cordless BT 1D Laser Barcode Reader	Tracient Cordless HF RFID Reader

Issued by: H.C. Lee

Released Date: 11/04/2008

Rev. R04