

gotive[®] SQ31

Rugged Communicator

with • Bar Code Reader

- WLAN connectivity
- VoIP Phone capability

Fits any Hand

- True handy design
- All day wearable weight

Suits any Environment

- From dusty warehouse to chic boutique
- Bright colour LCD with touchpad
- Weather and drop resistant
- Rugged construction

Real Groupware Solutions

- Product line covering all aspects of group comfort
- Organised storing and charging

Simple to Use

- Intuitive and ergonomic interface
- Easy to hold shape

Powerful

- Intel XScale PXA270
- 128 MB RAM
- 1 GB Flash
- Windows CE 5.0
- 2400 mAh Li-Ion Battery

... and Emotional Value Added[™]

Shaping the Difference: Rugged with Style[™]



Communicators for Mobile Enterprise

Technical Specification

Physical Characteristics	
Dimensions	144 x 72 x 37 mm (5.67 x 2.83 x 1.45 in)
Weight	230 g incl. Battery Pack (8.1 oz)
Environment Sealing	IP54
Drop Specification	1.2 m (4ft.)
Storage Temperature	-20 to 60°C
Operating Temperature	-10 to 50°C (Battery Pack charging range: 0 to 45°C)
Relative Humidity	5% to 95% non-condensing
Key Hardware	
CPU	Intel® XScale PXA270, 520 MHz
Memory	1 GB non-volatile Flash, 128 MB RAM
Memory Expansion	miniSD card slot, user-accessible
Display & Touch screen	2.8" QVGA 240x320 pixels, 64k colours, Bright colour transmissive LTPS TFT, Transmissive Positive Micro Reflective (TMR), integrated 4-wire analogue resistive touchpad, dynamic landscape/portrait operation switch
Keyboard	rubber, 3 programmable buttons
Buttons	2 x 2 programmable side Action Keys, suspend button, reset button
LED indicators	3 indicators: system status, Wireless LAN status, charging status
Sound	16 bit sound, 1 receiver/speaker, 1 microphone, 1 buzzer
Power	internal user-swappable/rechargeable 2400 mAh Li-Ion Battery Pack, 8.9 Wh external variety of charging accessories
Communication	
Wireless LAN	802.11b/g, internal antenna
USB	full-speed Host/Client (USB 1.1)
Sound	external headphone and microphone interface
Data Capture	
Bar Code Reader	integrated 1D CMOS Imager (Intermec EV12)
Key Software	
Operating System	Windows® CE 5.0
Development Environment	Gotive SQ31 SDK for Visual Studio .NET (Visual Basic .NET, C#) and Embedded Visual C++
SDK	Gotive specific API functions available for: Bar Code Reader LCD Backlight Control, Rotation Free Programmable Action Keys Electrical Lock (E-Lock), Docking Station ID Buzzer .NET Compact Framework Standard APIs for Windows® (Windows® CE.NET)
Terminal Emulator	Windows® Terminal Services, optional 3rd party software
Microsoft® Applications	Internet Explorer 6.0 for CE, WordPad
Browser Plug-ins	Macromedia®Flash® 6.0 Plug-in enabled Microsoft® Windows® Media Player Java Support via 3rd party software
Software Update	via miniSD Card, USB or Wireless LAN
Backup Application	Backup Manager
PC Connectivity	Microsoft® ActiveSync/Windows Mobile Device Center
Accessories	
Organised Storing & Charging	Multi Purpose Station (various configuration options available)
Power	internal Battery Pack - Li-Ion 2400 mAh external Multi Purpose Station (various configuration options available) Travel Plug (USB/charging/audio/carrying)* with Neck Stripe and Belt Loop Simple Docking Station (USB/charging)
Data Connectivity	Travel Plug (USB/charging/audio/carrying)* Simple Docking Station (USB, charging)
Ergonomy & Operability	Carrying Plug with Neck Stripe and Belt Loop Pen Stylus
* ask for availability	

Business partner:

For more information contact sales@gotive.com or visit www.gotive.com

In continuing effort to improve our products, Gotive a.s. reserves the right to change designs and specifications without prior notice. Gotive is a registered trademark of Gotive a.s. Microsoft, Windows, Windows CE, ActiveSync are trademarks of Microsoft Corporation in USA and/or other countries. Other product and company names mentioned herein may be trademarks of their respective owners. Copyright © 2006-2007 www.gotive.com All rights reserved. No part of this project may be reproduced by any means without written permission of its authors. GO.034.01.01.EN ver.241108